



PA720

Enterprise Digital Android Assistant

The PA720 rugged handheld computer revolutionize the way you do business.

Compact design but powerful - The Unitech PA720 enterprise digital assistant brings performance, durability and speed into a distinctive device. Powered by the latest Android 5.1 operation system (soon available to upgrade to 6.0) and a 64-bits quad-core processor. In addition, the PA720 has a 4G LTE wireless communication technology and integrated 1D/2D barcode scanner that is aggressive and accurate. It is a versatile data collection tool for every need in the enterprise solutions.

Rugged, sleek and stylish

Built with a 4.7" color multi-touch display, supporting water rejection and wet finger tracking, stylish rounded edges design and weight of less than 287g (with battery), this PA720 is portable to take around anywhere you go.

Engineered with industrial grade materials and enhanced with a Gorilla Glass 3 screen (7H hardness) to keep it scratch free, the PA720 is rugged enough to drop from 1.5 meters onto concrete. This device is able to survive in harsh environments with its IP65 waterproof and dust-proof rating.

High Productivity with Superior Performance

The PA720 runs on Android 5.1 (and optional 6.0 upgrade) operating system. This allows users to develop in an open source platform with thousands of enterprise grade applications. In addition, the PA720 includes an integrated an advanced 64-bit quad-core CPU (1.3GHz) and plenty of RAM and power for your business applications.

This device is also equipped with a powerful Cryogenics Circuit Design battery that provides 3x longer operating time when used below -20°C, an 8 megapixel rear-facing camera, 5 megapixel front-facing camera and superior 1D and 2D barcode reader.

Blazing-fast 4G LTE network

Designed to be used in the work environment, PA720 offers blazing-fast 4G LTE network, WiFi 802.11 a/b/g/n, which enables users to download files from the internet up to 10 times faster than with 3G. Moreover, it also supports GPS, NFC and Bluetooth 4.1.

User-Friendly Functionality

The PA720 is constructed for field service workers and business-critical applications. In order to be user-friendly, this device not only built in an easy hot-swap battery design that allows users to change batteries without having to power off the devices, but also is equipped with a zero shutter lag time function that improves the lag between clicking the camera and barcode scanning to speed up the picture taking process.

Furthermore, the PA720 is implemented with physical function buttons and is supported by versatile MDM (mobile device management) systems such as MCL5, SOTI, 12Manage and MoboLink which offers a more efficient experience and maximize the productivity in the enterprise.

Main features

- Unparalleled performance with **64-bit quad-core processor** (1.3GHz)
- 4.7" HR display supporting water rejection and wet finger tracking
- Integrated superior 1D/2D barcode imager
- Great **ergonomic scanning comfort**; 15° downwards scanner angle
- Advanced battery **Cryogenics Circuit Design**; provides 3x longer operating time when used below -20°C (compared to a traditional design battery)
- Easy **Hot-swap battery** design without downtime
- Support blazing-fast **4G/LTE** and **2.4Ghz / 5Ghz** wireless communication
- Wide range of professional accessories
- Zero shutter lag time: Speed up the picture taking process
- Device supported versatile **MDM systems**: MCL5, SOTI, 12Manage and MoboLink

unitech
because we care





V2.0 PA720 Specifications

Operation System

| | |
|-------------------|---|
| CPU | 64-bits Quad Core 1.3GHz Processor |
| Memory | 3GB RAM 16GB Flash |
| OS | Supports Micro SD (2GB to 32GB) Android 5.1 (optional upgrade 6.0) |
| Languages support | English, Simplified Chinese, Traditional Chinese, Japanese, Spanish, German, French, Italian, Portuguese, Korean and multiple languages |

Display

Gorilla Glass 3 with 5-point Capacitive Touch Panel
4.7" Color LCD 720x1280 High Resolution Display
Supporting water rejection, wet finger tracking & readable in sunlight

Keypad

4 Function Keys, Push-to-talk key, Volume up/down key, Left/right scan key, Power key.

Camera/Photos/Video

8MP Rear Camera
5MP Front Camera
LED flash light

Indicator

Vibrator
3 color LED to indicate charge, scan and message

Symbologies

| | |
|-----------|---|
| 1D CCD | UPC-A/E, EAN-8/13, Codabar, Code 39, Code 39 Full ASCII, Code 93, Code 32, Interleaved & Std. 2 of 5, EAN 128, Code 11, Delta, MSI/Plessey, Code 128, Toshiba, RSS Expanded, RSS Limited, RSS14. |
| 2D imager | PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR Code, Micro QR Code, Aztec, MaxiCode, Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal Dutch Postal (KIX). |

RFID/HF

Frequency: 13.56MHz
Tag Support: ISO15693, ISO14443A, ISO14443B
Support NFC

Communication

| | |
|---------------|--|
| Interface | USB 2.0 w/ Pogo Pin |
| USB | USB 2.0 |
| WLAN | IEEE 802.11 a/b/g/n |
| Bluetooth | Bluetooth 4.1 BLE supported |
| WWAN 4G LTE | 2G – GSM: GSM850, EGSM900, DCS1800, PCS1900 3G – UMTS: Band 1, Band 2, Band 5, Band 8 4G – LTE: FDD Band 1(2100), Band 2(1900), Band 3(1800), Band 5(850), Band 7(2600), Band 8(900), Band 20(800) TDD: Band 38(2600), Band 39(1900), Band 40(2300), Band 41(2500) |
| GPS | GPS/ GNSS/ BDS |
| Other Sensors | Light, Proximity, eCompass, G-sensor |

Power Source (Hot Swappable)

| | |
|------------------|---|
| Main battery | 3.6V 3120mAh Lithium-ion - Cryogenics Circuit Design battery. This battery provides 3x longer operating time when used below -20°C (compared to a traditional design battery) |
| Extended battery | 3.6V 4660mAh |

Audio

1W Speaker 85 dB at 10cm
3.5mm Audio Jack
Receiver
Microphone

Expansion Slot

MicroSD Support MicroSD memory card up to 32GB

Enclosure

Weight 287g (with standard battery)
Dimension 170 mm x 30.4 mm x 81.2 mm

Environmental

| | |
|--------------------------|--------------------------------|
| Operating temperature | -20°C to 50°C |
| Storage temperature | -30°C to 60°C |
| Relative Humidity | 5% ~ 95% (non-condensing) |
| Drop Specification | 1.5m |
| Sealing | IP65 |
| Vibration and Shock test | MIL-STD-810F, 514.4 Process II |

Accessories

4-slot Ethernet Cradle
4-slot Terminal Charging Cradle
1-Slot USB Cradle
1-Slot Ethernet Cradle
USB Holder Cable
Main Battery
Extended Battery
Vehicle cradle

(Visit <http://eu.ute.com> to discover our full range of accessories.)

Regulatory Approvals

CE, NCC, FCC, BSMI, VCCI, CCC, RoHS compliance

Device supported MDM



UnitCare's service program

UnitCare 2.0 offers customers a high level of security by a reliable, high-quality and effective program for getting your devices serviced quickly. It also drives the hidden costs out of your installations. UnitCare goes beyond the standard warranty with a complete service offer for different need. **More information: unitcare.unitech.eu.**

Unitech Europe

Tilburg, The Netherlands
• Tel.: +31 (0)13 460 9292
• Email: Info@eu.ute.com
• Website: <http://eu.ute.com>



Unitech America

Unitech Asia Pacific

Unitech China

Unitech Europe

Unitech Japan

Unitech Taiwan

unitech
because we care