

B-452-TS

Versatile Desktop Printer



Perfect for Most Applications

The B-452-TS printer is fitted with a 300 dpi printhead with 4" print width and 4" per second print speed which guarantees excellent printing quality for a wide variety of labelling requirements.

Robust and Flexible

The compact and reliable B-452-TS thermal transfer/direct thermal printer can be controlled from a PC, a network or a stand-alone keyboard for ease of use. It supports all popular barcode symbologies and has been designed to meet all of your present and future needs.

B-452-TS



A Complete Labelling Solution

The B-452-TS12-QP-PAC comes with everything in the box to produce labels - demonstration labelling software, sample ribbon and labels, Windows drivers, parallel cable and owners manual.

Specifications

| | |
|---------------------|---|
| Technology | Thermal transfer / Direct thermal |
| Printhead | Flat type |
| Resolution | 11.8 dots/mm (300 dpi) |
| Print Width | Maximum 105.7 mm |
| Print Length | 15 to 500 mm |
| Print Speed | Up to 101.6 mm/sec (4 ips) |
| Interfaces | RS-232C, Centronics, Expansion I/O*, TCP/IP*, Keyboard I/F |
| Barcodes | UPC/EAN/JAN, Code 39, Code 93, Code 128, NW7, MSI, Industrial 2 of 5, ITF, Postnet, RM4SCC, KIX-code |
| 2D Codes | Data Matrix, PDF 417, Maxicode, QR code, Micro PDF 417 |
| Fonts | Times Roman (6 sizes), Helvetica (6 sizes), Presentation (1 size), Letter Gothic (1 size), Prestige Elite (2 sizes), Courier (1 size), OCR (2 types), Outline font (7 types), Writable character (44 fonts), TrueType Fonts (20 types)* |
| Optional | Swing cutter module, strip module, LAN I/F module, expansion I/O port, keyboard KB-80, TrueType font kit |
| Dimensions | 270 (W) x 200 (D) x 245 (H) mm (Without supply holder unit) |
| Weight | 4.7 Kg (Without media and ribbon) |

* Option

Options

The B-452-TS can be enhanced with:

| | |
|--------------------------------|---|
| Cutter module | A swing cutter to physically separate labels or continuous media immediately after printing. |
| Strip module | Peels the label from its backing paper and presents it ready for immediate application. |
| Stand-alone Keyboard | A unit that can be attached to the printer, call up pre-programmed label formats and enter data to print labels without requiring connection to a computer. It also can be used for viewing and setting the on-board diagnostics. |
| Expansion I/O interface | An additional port allowing the connection of an external device that requires signals from the printer, e.g. a barcode scanner or on-line verifier. |
| LAN interface | For connecting the printer to an Ethernet network. |
| Fonts | 20 downloadable TrueType Fonts. |

Your TOSHIBA TEC dealer:

