

## Product Profile



- Lightweight, ergonomic design allows for single-handed operation
- Choices of integrated bar code scanner or imager
- Large 160 x 160 display for flexibility in application design
- Customize with a flexible rapid development tool
- Linux® based operating system
- Powerful 67 MHz processor to support large look-up tables or data storage
- Choice of data communication docks

### CK1 HANDHELD COMPUTER

Companies of all sizes can now realize the benefits of automatic data collection with the CK1, a powerful and flexible batch data collection terminal for retail, light industrial, and medical/pharmaceutical applications requiring small-sized ergonomics at an economical price. With choices of simplified programming tools or pre-loaded applications, linear imager or bar code scanner, along with large memory and a crisp display, Intermec's CK1 can benefit the bottom line through increased employee productivity and inventory accuracy.

The CK1 offers features and functionality found in terminals much larger and more costly. With an ergonomic keyboard and a pocket-sized form factor, the CK1 allows for easy single-handed operation when it is demanded. An optional removable pistol grip handle is available for scan intensive applications.

The CK1 has a choice of bar code input options: an integrated laser scanner, or a highly responsive linear imager, offering safe user interaction and aggressive decoding performance. The large, scratch-resistant 160 x 160 pixel display with backlight provides user-friendly navigation in all lighting conditions, as

well as flexibility in application design. Continuing the Intermec legacy of rugged construction, the CK1 withstands multiple 1.2-meter (4-ft) drops to a hard surface.

Users will appreciate the simplicity of pre-written batch applications, powerful rapid application development tools or extensive SDK for flexible application choices offered by the CK1. It combines a Linux® based operating system and Linux® programming tools to provide a powerful and flexible open source platform for rich end-user applications with multi-tasking capabilities. Use CK1 right out of the box with pre-written programs for various applications, or for powerful and rapid application development, a Windows® based rapid development tool can be purchased that requires no programming experience.

Intermec's CK1 has a powerful ARM 7, 67 MHz processor with 16MB DRAM and 9MB Flash to support large look-up tables or data storage. A replaceable Lithium-Ion battery supports extended rigorous use and a fast 3-hour recharge.

Numerous docking options are available including a single-slot RS-232 or modem dock and a multi-slot USB charging dock.

**Physical Description**

The ergonomic, pocket-sized CK1 is a fully functional Linux based computer for efficient, automated batch data collection. With large display, and choice of integrated bar code scanner or linear imager, the CK1 is ideal for parcel pickup and delivery, light industrial, and retail inventory management.

**Physical Characteristics**

**Length:** 190 mm (7.5")

**Height:** 35 mm (1.35")

**Width:** 73 mm (2.88")

**Depth:** N/A

**Weight:** 218 g (7.68 oz.) including battery

**Power**

**Supply:** 900 mAh (3.6V) rechargeable

Lithium Ion (Li-Ion) battery pack

**Battery Life:** Extended shift (12 hour)

**Power Management:** Auto-suspend

**AC Adapter/Recharging:** 3-4 hour recharge time

**Environment**

**Operating Temperature:** -10° to 60° C

(14° to 140° F)

**Storage Temperature:** -20° to 70° C

(-4° to 158° F)

**Recharging Temperature:** 0° to 50° C

(32° to 122° F)

**Humidity:** 0 to 95% relative humidity (non-condensing)

**Rain and Dust Resistance:** Designed to IP42

**Drop Survival:** Designed for multiple 1.2m (4-ft) drops to concrete

**Hardware**

**Memory:** 16MB DRAM

**Non-volatile Flash Memory:** 9MB

**Microprocessor:** 67 MHz ARM 7 Processor

**Operating System:** Embedded Linux

Operating System, EsFia uLinux

Version 2.4

**Display:** Monochrome, anti-glare LCD display capable of configurable graphics and supporting up to 16 lines by 20 characters (160 x 160 pixels) with auto-off EL backlighting and scratch resistance surface.

**Keyboard:** 29 hard top keys including single Enter/Scan button, Numeric keys, with shift alpha, 4 navigation keys and 4 function keys

**Beeper:** User programmable volume, pitch and duration

**LED:** Tri-state software programmable LED to indicate good/bad read/communication

**Software**

**Development Environments:**

Microsoft® C application development under Windows 2000, XP

Software Development Kit (SDK)

MCL Rapid Development Tool Kit for

application program development

**International Support**

English / Western European languages

Japanese, Traditional Chinese (Big 5),

Chinese Simplified, Thai (future)

**Connectivity**

**TCP/IP over PPP using the following transports:** RS232 direct single dock, USB multi dock, RS232 modem or \*Bluetooth™.

TCP/IP over PPP GPRS using either a Bluetooth or tethered GPRS mobile phone.

Z-Modem communication protocols using either RS232 direct single dock, USB multi dock, RS232 modem or Bluetooth.

**Security**

Administrative password protection optional

**Bar Code Symbolologies**

Code 39 Standard and Full ASCII, Codabar, UPC/EAN, UCC/EAN128, Interleaved 2 of 5, Code 32, Standard 2 of 5, Code 93, Code 128, MSI, Plessey, China Postal Code, RSS14

**Characters/Fonts**

Font 1: Courier 6x8, 20 lines, 26 columns

Font 2: Courier 8x16, 10 lines, 20 columns

**Bar Code Scanning Module Options**

Integrated Linear Imager

Integrated Standard Range Visible Laser (650nm)

**Scanning Performance**

**Scan rate:** Linear Imager – 270 scans/second

**Scan rate:** Visible Laser – 39 scans/second

**Wireless PAN**

Optional integrated Bluetooth™ compatible module (Serial Port Profile)

**Accessories**

**Communication/Charge Dock:** Single RS-232, V90 Modem

**Multi-Dock:** Four Cavities (Daisy Chain) USB Wrist Strap (Standard)

Scan Handle

Single Battery Charger

Cell Phone data cable

Printer cable

**Regulatory Approvals**

**Electrical:** CE Compliance

**Emissions:** FCC Part 15 – Class A

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.

\*Bluetooth is a trademark owned by Bluetooth SIG, Inc., USA.

**Intermec®**  
e x p e c t MORE™

Copyright © 2003 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611405-01A 11/03

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

Switzerland • **OPAL Associates AG** • Motorenstrasse 116 • CH-8620 Wetzikon • Telefon +41 (0)1 931 12 22 • Telefax +41 (0)1 931 12 20 • Email info@opal-holding.com • URL <http://www.opal.ch/> • **OPAL Associates SA** • Avenue des Boveresses 54 • Case postale 29 • CH 1000 Lausanne 21 • Telefon +41 (0)21 653 95 00 • Telefax +41 (0)21 653 95 02 • Email info@opal-holding.com • URL <http://www.opalsa.ch/> • **Germany • OPAL Associates GmbH** • Lohnerhofstrasse 2 • D-78467 Konstanz Telefon • +49 (0)7531 813 000 • Telefax +49 (0)7531 813 00 99 • Email info@opal-holding.com • URL <http://www.opalgmbh.de/> • **OPAL Associates GmbH** • Osterholder Allee 2 • 25421 Pinneberg • Telefon +49 (0)4101 787 615 • Telefax +49(0)4101 787 616 • Email info@opal-holding.com • **OPAL Solutions GmbH** • Wilhelmstr. 22 • 52428 Jülich • Telefon +49 (0)2461 936 770 • Telefax +49(0)2461 936 771 • Email info@opal-holding.com • URL <http://www.opal-solutions.de/> • **Austria • OPAL Associates GesmbH** • Vorarlberger Wirtschaftspark • A-6840 Götzis • Telefon +43 (0) 5523 58833 • Telefax +43 (0)5523 521569 • Email info@opal-holding.com • URL <http://www.opalgmbh.at/>

