

## CRD21

Cradle for H21



### + Specifications

#### Communication

- USB: Ver. 1.1, client, USB-A connector

#### Power

- Voltage requirement: 5V
- Charging method: Battery in terminal or in spare slot

#### Durability

- Temperature in operation: 5 to 40 °C / 41 to 104 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F

#### Physical

- Dimensions (w x h x d): 80 x 55 x 70 mm / 3.15 x 2.17 x 2.76 in
- Weight body: Ca. 65 g / 2.3 oz
- Case: ABS, Black

#### Regulatory & Safety

- Product compliance: CE, RoHS

#### Enclosed items

- USB cable
- Power supply 100-240V/0.4A, 50/60 Hz, 5V/2A

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp
- **France:** Issy Les Moulineaux
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Renton, WA
- **Japan:** Warabi City

- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariong
- **Brazil:** São Paulo

Opticon Sensors Europe B.V  
European headquarters  
Opaallaan 35  
2132 XV Hoofddorp  
The Netherlands  
phone: +31 (0)23-5692700  
fax: +31 (0)23-5638266  
email: sales@opticon.com  
internet: www.opticon.com