

**Product Profile**



- Intermec Designed & Manufactured
- Dual high capacity Lithium Ion batteries
- Intermec SmartSystems™ Device Management
- Serial, USB and Bluetooth® Class 1 Interfaces
- Frontloading batteries
- Flexibility to use roll or fanfold receipt paper
- High visibility buttons and indicators
- International logos facilitate global use
- Simple paper installation
- Operates in temperatures as low as -20° C

**P B 4 2 P O R T A B L E P R I N T E R**

Intermec's PB42 four inch wireless portable receipt printer is designed to improve direct store delivery (DSD), Field Service, and Home Utility applications. The PB42 printer interfaces seamlessly with the CK60 and 700 Intermec handheld computers. Daily route activities are easily entered and tracked via a mobile computer throughout a workers shift. Receipts are immediately provided to the customer for prompt payment or to eliminate duplicate billing efforts.

The unique Intermec design of the PB42 portable receipt printer ensures ease of use. This is very important for delivery drivers who negotiate routes with multiple stops and rugged conditions. Special design features include sharing of battery design with the CK60 mobile computer, simple receipt paper installation, high visibility buttons and indicators to show when the printer is within radio range or when the lithium

ion batteries are getting low. Charge up to four printers at once with the unique four bay charger. Printers "drop-in" and charge from hinge pins; no charge cable required. Frontloading batteries that can be removed with just one hand. Lexan® media windows conveniently show media status. Standard belt clip & hand strap also add to the convenience of operation.

The Intermec Ready-to-Work Indicator is integrated into the PB42 printer. This is part of the Intermec SmartSystems™ and provides a visual cue to the operating state of the printer.

Intermec's PB42 portable receipt printer is ideal for use worldwide. The PB42 printer features widely recognized international logo indicators on the buttons, multiple language character sets, and worldwide certifications. The PB42 printer is ideal for streamlining processes and route deliveries in DSD, field service, and home utility industries worldwide.

**Application**

Thermal receipt printing

**Physical Characteristics**

**Depth:** 3.1 inches (7.87 cm)

**Height:** 7.1 inches (18.03 cm)

**Width:** 6.62 inches (16.82 cm)

**Weight:** 3.0 lb (1.36 kg) w/ 2 battery

packs and full roll receipt paper

**Drop test:** 4 ft to concrete

**Print Specifications**

**Print Width:** 4.1 inch (104 mm)

**Element Size:** 0.0049 inch (0.125mm)

**Minimum Graphical Element:** 0.010 inch (0.254 mm)

**Print Speed**

2 ips (50 mm/sec)

**Print Resolution**

203 DPI (8 dots/mm)

**Receipts**

**Max. Width:** 4.4 inch (111.8 mm)

**Thickness:** 0.002 to .0044 inch (0.05 to 0.112 mm)

**Tracking:** Center

**Style:** Roll-fed or fanfold

**Label Roll Max Diameter:** 2.65 inches (67 mm)

**Label Roll Core ID:** 0.75 inch (19.05 mm)

**Media Type:** Receipt paper

**Standard Interface**

- Serial RS-232 (115 kbps)
- USB v.1.1 (full speed)
- Class 1 Bluetooth®

**Optional Interface**

- Class 1 Bluetooth™ - range up to 100 m (328 feet)

**Character Sets**

- West European Latin No. 1 and 9: Danish, Dutch, English, Faeroese, Finnish, French, German, Icelandic, Irish, Italian, Norwegian, Portuguese, Spanish, and Swedish.
- East European Latin No. 2: Albanian, Czech, English, German, Hungarian, Polish, Rumanian, Serbocroatian, Slovak, and Slovene.
- Cyrillic: Bulgarian, Byelorussian, English, Macedonian, Russian, Serbocroatian, and Ukrainian.
- Arabic
- Greek
- Hebrew
- U.S. standard
- Europe multilingual
- Code Page requirements for Far East

Log onto [www.intermec.com](http://www.intermec.com) for additional international fonts for the PB42 portable printer.

**Font types**

40 column, normal, bold, 80 column, normal, bold, 132 column, normal, bold

**Standard Memory**

- 16 MB SDRAM
- 4 MB Flash

**LED Indicators**

- Intermec Ready-to-Work Indicator
- Radio – Green Flashing
- Battery – Green/Red

**Power Supply**

**AC Adapter:** 50 Watt

**Voltage Range:** 12 V ± 5%.

**Rechargeable Li-Ion Battery:** 7.2V, 2.4A-H. Each printer ships standard with two batteries (batteries do not ship with vehicle mount option).

**Operating Environment**

**Operating:** -20°C (-4°F) to 50°C (122°F)

**Non-operating:** -30°C (-22°F) to 70°C (158°F)

**Battery Charging:** 0°C (32°F) to 50°C (122°F)

**Relative Humidity:** 10% to 90% non-condensing

**Regulatory Approvals**

North America UL and cUL Listed, UL 60950; Europe TÜV Rheinland GS Licensed, EN 60950; Mexico NYCE CERTIFIED, NOM 19; Other Countries EN 60950 CB; CE Mark

**EMC Approvals**

USA FCC Title 47, Part 15, Subpart B, Class B; Europe EMC Directive (EN 55022 Class B + EN 55024); CISPR22

**Options & Accessories**

Belt Clip, Shoulder Strap, Batteries, AC Charger, Vehicle Mount, External Paper Tray, AC Power Adapter, Cigarette Lighter Adapter, Nylon System Case, Four Bay Printer Charger

**North America**

**Corporate Headquarters**  
6001 36<sup>th</sup> Avenue West  
Everett, Washington 98203  
tel: 425.348.2600  
fax: 425.355.9551

550 2nd Street S.E.  
Cedar Rapids, Iowa 52401  
tel: 319.369.3100  
fax: 319.369.3453

**Media Supplies**  
9290 Le Saint Drive  
Fairfield, Ohio 45014  
tel: 513.874.5882  
fax: 513.874.8487

**Canada**

7065 Tranmere Drive  
Mississauga, Ontario  
L5S 1M2 Canada  
tel: 905.673.9333  
fax: 905.673.3974

**Europe/**

**Middle East & Africa  
Headquarters**  
Reading International Business Park  
Basingstoke Road  
Reading RG2 6DD  
United Kingdom  
tel: 44.118.923.0800  
fax: 44.118.923.0801

**Asia**

**Asia Regional Office**  
26-16 International Plaza  
10 Anson Road  
Singapore 079903  
tel: 65.6324.8391  
fax: 65.6324.8393

**Beijing Representative Office**

29 FL, Unit A1, China Merchant Tower  
118 Jian Guo Road  
Chaoyang District, Beijing 100022  
Tel: 86.10.5165.5922  
Fax: 86.10.6567.6778

**Australia**

Level 4, 1-3 Atchison Street  
St. Leonards, NSW 2065  
Australia  
tel: 61.2.9330.4400  
fax: 61.2.9437.0204

**South America & Mexico**

**Intermec South America Ltda.**  
Rua Samuel Morse 120 9 andar  
Brooklin CEP04576-060  
São Paulo, SP  
Brazil  
tel: 55.11.5502.6770

**Intermec Technologies de Mexico**

Av Tamaulipas #141, Primer Piso  
Col. Hipodromo Condesa  
Mexico, DF, 06140 Mexico  
tel: 525.55.241.4800  
fax: 525.55.211.8121

**Internet**

[www.intermec.com](http://www.intermec.com)

**Sales**

800.934.3163  
(toll free in N.A.)  
tel: 425.348.2726

**OEM Sales**

tel: 425.348.2762

**Customer Service and Support**

800.755.5505  
(toll free in N.A.)  
tel: 425.356.1799

Copyright © 2006 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611578-011 05/06

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

