

AP 300 Access Port

symbol
The Enterprise Mobility Company™

**Next-Generation Access Ports:
More Functionality at a Lower Cost**

WIRELESS LANS

More Functionality for a Fraction of the Cost of Access Points

Access Ports are a key component of Symbol Technologies' award winning Wireless Switch System, the second-generation wireless LAN architecture that does more, yet costs less. Working in conjunction with Symbol's Wireless Switch 2000, the AP 300 Access Port delivers robust and feature rich IEEE 802.11a/b/g connectivity. Access Ports substantially reduce the cost of deploying, implementing and managing a wireless LAN, while significantly increasing features, functionality and security of the wireless LAN infrastructure.

Virtual AP Enables True RF Virtual LANs (VLANs) for Better Device and Network Performance

With Virtual AP, each Access Port can support four separate wireless broadcast domains—functionality that would otherwise require the installation of four first-generation access points. These true wireless VLANs enable separation of mobile end-users, ensuring that broadcast traffic reaches only those recipients for which it is intended. Overall network traffic is reduced, network and device performance is improved, and device battery life is increased—at a fraction of the cost required to deliver the same functionality in a first generation access point-based network.

Each AP 300 supports four BSSIDs (Basic Service Set Identifiers) and 16 ESSIDs (Extended Service Set Identifiers) per radio, enabling granular segmentation of the wireless LAN into multiple broadcast domains to meet specific enterprise needs. Typical access points support only one BSSID, utilizing ESSIDs (instead of BSSIDs) to create wireless VLANs.

Dual-radio 802.11a and 802.11g Design

Simultaneous service to 802.11a, 802.11b and 802.11g mobile devices provides high-bandwidth wireless connectivity at speeds of up to 54 Mbps in both the 2.4 GHz and 5.2 GHz ISM bands.

Thin AP Design

The AP 300, as all other Symbol Access Ports, requires no configuration or manual firmware maintenance. The Symbol Wireless Switch discovers Access Ports on the network and automatically downloads all configuration parameters and firmware. Installation, maintenance and troubleshooting costs are greatly reduced.

For more information, contact Symbol at +1.800.722.6234 or +1.631.738.2400, or visit us on the web at: www.symbol.com



| Features | Benefits |
|--|---|
| Dual form-factors | Plenum-rated external antenna model with metal housing is ideal for installation above ceiling tiles; the plastic internal-antenna housing allows for installation within the 'carpeted-space' and provides cost-effective coverage via the integrated 2.4 GHz and 5.2 GHz antennas |
| Interoperability | Standards-based wireless, wired and security protocols ensure interoperability with third-party hardware |
| 802.1x supplicant | Allows authentication to a RADIUS server to enable an 802.1x-protected Ethernet port |
| 802.11h | Enables worldwide operation through support for standards-based dynamic frequency selection and power control |
| 802.11i | Support for IEEE standards-based security protocols for strong Encryption (AES, TKIP), Authentication and Key Management (802.1x-EAP) |
| Flexible mounting options | Fast and easy installation with wall, ceiling and above-ceiling tile mounting options; internal antenna version snaps on to T-bars of suspended ceilings without the use of any hardware; external antenna version installs above ceiling tiles |
| 802.3af | Simplifies and reduces total cost of installation through support of standards-based Power-over-Ethernet (PoE) |
| Load Balancing, Pre-emptive Roaming and Rate Scaling | Increases reliability and resilience of the wireless network to support mission critical applications |

AP 300 Specification Highlights

| Physical Characteristics | AP 300 (internal antenna) | AP 300 (external antenna) |
|---|--|---|
| Dimensions: | 9.5 in. L x 7.0 in. W x 2.0 in. H/24.1 cm L x 17.8 cm W x 5.1 cm H | 9.25 in. L x 5.75 in. W x 1.0 in. H/23.5 cm L x 14.6 cm W x 2.54 cm H |
| Weight: | 1.0 lbs./0.45kg | 1.6 lbs./0.73kg |
| Part Number*: | WSAP-5110-100-WW | WSAP-5100-100-WW |
| Available Mounting Configurations: | Ceiling-Mount (to suspended ceiling T-bars, below tile); Wall Mount | Ceiling-Mount (above tile); Wall-Mount |
| Plenum Rated: | No | Yes, certified to UL 2043 |
| LEDs Indicators: | 2 LED indicators with multiple modes indicating 802.11a/802.11g Activity, Power, Adoption and Errors | |
| Wireless Data Communications | | |
| Data Rates Supported: | 802.11a: 6, 9, 12, 18, 24, 36, 48 and 54 Mbps; 802.11b/g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, 54 Mbps | |
| Network Standard: | 802.11a, 802.11b, 802.11g | |
| Wireless Medium: | Direct Sequence Spread Spectrum (DSSS) and Orthogonal Frequency Division Multiplexing (OFDM) | |
| Uplink: | Auto-sensing 10/100Base-T Ethernet | |
| Radio Characteristics | | |
| Frequency: | 802.11b/g: 2.412 GHz to 2.484 GHz; 802.11a: 4.9 GHz to 5.875 GHz | |
| FCC (US and Canada): | 2.412 GHz to 2.462 GHz; 5.150 GHz to 5.250 GHz (UNII -1); 5.250 GHz to 5.350 GHz (UNII -2); 5.725 GHz to 5.825 GHz (UNII -3); 5.825 GHz to 5.850 GHz (ISM) | |
| EU: | 2.412 GHz to 2.472 GHz; 5.150 GHz to 5.250 GHz; 5.150 GHz to 5.350 GHz; 5.470 GHz to 5.725 GHz; (Country Specific) | |
| Japan: | 2.412 GHz to 2.484 GHz; 4.900 GHz to 5.000 GHz; 5.150 GHz to 5.250 GHz | |
| China: | 2.412 GHz to 2.472 GHz | 5.725 GHz to 5.850 GHz |
| Operating Channels: | 802.11b/g: ETSI: 13; North America: 11; TELEC (Japan): 13 802.11a: ETSI: Country Specific; North America: 12; UNII I, II, III; (approval for 5.4-5.7 GHz pending); TELEC (Japan): 8 | |
| Nominal Transmitter Power: | 802.11b/g: 17.5 dBm +/- 1 dBm @ 1, 2, 5.5, 11 Mbps; 17.0 dBm +/- 1 dBm @ 6 and 9 Mbps; 16.5 dBm +/- 1 dBm @ 12 and 18 Mbps; 14.0 dBm +/- 1 dBm @ 24 and 36 Mbps; 12.5 dBm +/- 1 dBm @ 48 and 54 Mbps 802.11a: 17.5 dBm +/- 1 dBm @ 6 and 9 Mbps; 16.0 dBm +/- 1 dBm @ 12 and 19 Mbps; 14.0 dBm +/- 1 dBm @ 24 and 36 Mbps; 12.0 dBm +/- 1 dBm @ 48 and 54 Mbps | |
| Receiver Sensitivity: | 802.11b: 11 Mbps @ -84dBm; 5.5 Mbps @ -87dBm; 2 Mbps @ -88dBm; 1 Mbps @ -90dBm 802.11g: 54 Mbps @ -68 dBm; 48 Mbps @ -70 dBm; 36 Mbps @ -75 dBm; 24 Mbps @ -79 dBm; 18 Mbps @ -81 dBm; 12 Mbps @ -85 dBm; 9 Mbps @ -87 dBm; 6 Mbps @ -88 dBm 802.11a: 54 Mbps @ -68 dBm; 48 Mbps @ -70 dBm; 36 Mbps @ -75 dBm; 24 Mbps @ -79 dBm; 18 Mbps @ -81 dBm; 12 Mbps @ -85 dBm; 9 Mbps @ -87 dBm; 6 Mbps @ -88 dBm | |
| User Environment | | |
| Operating Temperature: | 32°F to 104°F/0°C to 40°C | -4°F to 122°F/-20°C to 50°C |
| Storage Temperature: | -40°F to 158°F/-40°C to 70°C | |
| Operating Humidity: | 5%-95% (non-condensing) | |
| Operating Altitude: | 8000 ft./2438 m | |
| Storage Altitude: | 15000 ft./4572 m | |
| Electrostatic Discharge: | +/- 15 kV (Air), +/- 8 kV (Contact) | |
| Power Specifications | | |
| Operating Voltage: | 48 VDC @ 7W (Typical), 36 VDC to 57 VDC (Range) | |
| Operating Current: | 145mA @ 48VDC (typical) | |
| Integrated Power Over Ethernet Support: | Standards-based IEEE 802.3af | |
| Antenna Specifications | | |
| Type: | Integrated 2.4 GHz and 5.2 GHz Dual-Antenna; Elements with diversity | Two RSMA and two RBNC connectors for external antennas (not included) |
| Band: | 2.4 GHz to 2.5 GHz; 4.9 GHz to 5.850 GHz (actual operating frequencies depend on regulatory rules and certification agency) | |
| VSWR: | 2.4 GHz: Less than 2:1; 5.2 GHz: Less than 1.5:1 | (antenna-specific) |
| Gain: | 2.4 GHz: 0.0 dBi; 5.2 GHz: 3.0 dBi | (antenna-specific) |
| Regulatory | | |
| Product Safety Certifications: | UL 60950, cUL, EU EN 60950, TUV and UL 2043 (external Antenna) | |
| Radio Approvals: | FCC (USA), Industry Canada, CE (Europe) and TELEC (Japan) | |
| *WS-2000-1C-ABG-WW (1-Cell Package includes one WS-2000-SME-WW with one AP 300) | | |

Specifications are subject to change without notice. Symbol® is a registered trademark of Symbol Technologies, Inc. All other trademarks and service marks are proprietary to their respective owners.

For system, product or services availability and specific information within your country, please contact your local Symbol Technologies office or Business Partner.

Corporate Headquarters
Symbol Technologies, Inc.
 One Symbol Plaza
 Holtsville, NY 11742-1300
 TEL: +1.800.722.6234/+1.631.738.2400
 FAX: +1.631.738.5990

For Asia Pacific Area
Symbol Technologies Asia, Inc.
 (Singapore Branch)
 Asia Pacific Division
 230 Victoria Street #05-07/09
 Bugis Junction Office Tower
 Singapore 188024
 TEL: +65.6796.9600
 FAX: +65.6337.6488

For Europe, Middle East and Africa
Symbol Technologies
 EMEA Division
 Symbol Place, Winnersh Triangle
 Berkshire, England RG41 5TP
 TEL: +44.118.9457000
 FAX: +44.118.9457500

For North America, Latin America and Canada
Symbol Technologies
 The Americas
 One Symbol Plaza
 Holtsville, NY 11742-1300
 TEL: +1.800.722.6234/+1.631.738.2400
 FAX: +1.631.738.5990

Symbol Website
 For a complete list of Symbol subsidiaries and business partners worldwide contact us at:
www.symbol.com

E-mail
info@symbol.com



AP300DS 12/04

Part No. AP300DS Printed in USA 12/04 © Copyright 2004 Symbol Technologies, Inc. All rights reserved. Symbol is an ISO 9001 and ISO 9002 UKAS, RVC, and RAB Registered company, as scope definitions apply.

symbol[®]
 The Enterprise Mobility Company™