

## RUGGED HANDHELD SCANNER

### Value class rugged scanner delivers affordable durability

The LS3008 rugged handheld scanner offers affordable performance and durability in smaller manufacturing and light industrial environments. Built for all day every day use, the LS3008 provides the highest level of uptime performance in its class. Single board construction eliminates the common points of failure associated with ribbon cables that connect multiple boards. The patented Liquid Polymer Scan Technology is frictionless and will not wear out. The scanner is built to withstand everyday drops; offers a scratch-resistant, tempered glass exit window for high-quality scanning day in and day out; and can be safely used in dusty environments. In addition, the scanner offers the sealing required to endure wipe downs, and can even be sanitized in clean manufacturing and hospital environments.

### Superior functionality for superior productivity

This easy-to-use, lightweight and ergonomic device requires virtually no training and is packed with productivity enhancing features. Objects can be comfortably scanned at any angle — the innovative multi-line rastering scan pattern eliminates the need for exact aim and positioning of the scanner. Users can move rapidly from one bar code to another without delay or rescanning, due to superior motion tolerance. With optimized optics, the LS3008 helps deliver first time, every time scanning — even on damaged and poorly printed bar codes. And the ability to automatically switch between handheld and hands-free modes minimizes hand motion and user fatigue, while maximizing worker productivity.

### Low total cost of ownership

In addition to the productivity-enhancing features you need to keep business moving, the LS3008 offers a low total cost of ownership. The rugged design significantly reduces device downtime. Support for Remote Scanner Management (RSM) enables you to discover, provision and upgrade devices from a central remote location, dramatically reducing management time and costs. Multiple on-board interfaces provide true plug-and-play simplicity with your host system today, as well as tomorrow. And since even rugged devices require a support plan, Symbol's Service from the Start Advance Exchange Support contract provides next-business-day delivery of a replacement device for maximized uptime and productivity. This offering also includes Symbol's unique Comprehensive Coverage, which extends normal wear and tear to cover accidental damage to scan elements, exit windows, and other internal and external components at no extra charge — significantly reducing your unforeseen repair expenses.



#### FEATURES

#### BENEFITS

Single board construction	Eliminates the most common point of failure — ribbon cables between multiple circuit boards
Drop specification: 6.5 ft./2m drops to concrete at room temperature	Maximizes reliability and uptime
IP53 sealing	Can be safely wiped down and sanitized for clean manufacturing and hospital environments
Liquid Polymer Scan element with lifetime warranty	Eliminates friction and wear for superior durability and reliability
Wide working range from 0 to 19 inches	Enables comfortable, intuitive scanning
Ability to read down to 3 mil bar codes	Enables effortless scanning of smaller bar codes
Scratch resistant tempered glass exit window	Delivers continuously reliable scanning
Superior motion tolerance	Enables scanning of bar codes in rapid succession without delay; reduces fatigue and increases productivity
Multi-line rastering scan pattern	Delivers superior scanning performance; eliminates need for exact aim and positioning; captures even tiny, stacked and poorly printed bar codes
Multiple onboard interfaces including RS232, USB and KBW (keyboard wedge)	Simplifies installation and integration; ensures compatibility with host/POS today and tomorrow
Remote Scanner Management (RSM) support	Discover, provision and upgrade devices from a central remote location; dramatically reduces management effort and costs
Optional Intellistand for hands-free mode	Ability to switch between hands-free and handheld modes for maximum productivity and comfort

For more information on how the rugged LS3008 can boost productivity and reduce costs in your environment, contact us at +1.800.722.6234 or +1.631.738.2400, or visit us on the web at: [www.symbol.com/LS3008](http://www.symbol.com/LS3008)

## LS3008 Specification Highlights

### Physical Characteristics

Dimensions:	6.7 in. H x 3.7 in. L x 2.7 in. W 17 cm H x 9.3 cm L x 6.8 cm W
Weight:	Approximately 6.4 oz./181 gm
Voltage and Current:	5 +/- 10%VDC @ 140 mA (Stand by: <35 mA)
Color:	Yellow/Twilight Black

### Performance Characteristics

Light Source:	650 nm laser diode
Motor Frequency:	50Hz
Decode Rate:	200 decodes per second
Roll/Pitch/Yaw:	+/- 35°; +/- 60°; +/- 60°
Nominal Working Distance:	13 mil (100% UPC/EAN): 0 to 19 in. (48.25 cm) 5 mil (Code 39): 1.25 to 5.25 in. (3.17 to 13.33 cm)
Print Contrast:	25% minimum reflectance
Motion Tolerances:	Horizontal velocity: 200 in. (508 cm)/second Vertical velocity: 200 in. (508 cm)/second Angular velocity: 200 in. (508 cm)/second
Decode Capability:	UPC/EAN and with supplementals, Code 39, Code 39 Full ASCII, Tri-optic Code 39, RSS Variants, UCC/EAN 128, Code 128, Code 128 Full ASCII, Code 93, Codabar (NW1), Interleaved 2 of 5, Discrete 2 of 5 MSI, Codell, IATA, Bookland EAN, Code 32
Interfaces Supported:	RS-232C (Standard, Nixdorf, ICL, & Fujitsu); IBM 468x/469x; Keyboard Wedge; USB (Standard, IBM SurePOS, Macintosh); Laser/Wand Emulation; In addition Synapse Adaptive Connectivity allows for connectivity to all of the above plus many non-standard interfaces

### User Environment

Operating Temperature:	32° to 122° F/0° to 50° C
Storage Temperature:	-40° to 158° F/-40° to 70° C
Humidity:	5% to 95% non-condensing
Drop Specification:	Withstands multiple 6.5 ft./2 m drops to concrete at room temperature; 6 ft./1.825 m drops to concrete at all other operating temperatures
Environmental Sealing:	Sealed at IP53 against dust and water
Ambient Light Immunity:	Immune to normal artificial indoor and natural outdoor (direct sunlight) lighting conditions

### Regulatory

Electrical Safety:	Certified to UL1950, CSA C22.2 No. 950, EN60950/IEC950
EMI/RFI:	FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive, Australian SMA
Laser Safety:	CDRH Class II, IEC Class 2

### Accessories

Mounting Options:	Intellistand with adjustable height: 5 to 10 in./12.7 to 25.4 cm and adjustable angle between 0° to 90°; desktop and wall-mount holders; scanner sleeve with integrated loop for tether attachment
Power Supplies:	Power supplies are available for applications that don't supply power over the host cable

### Warranty

Subject to the terms of Symbol's hardware warranty statement, the LS3008 handheld scanner products are warranted against defects in workmanship and materials for a period of three (3) years from the date of shipment.

The Liquid Polymer Scan Element includes an unprecedented limited lifetime warranty.

For the complete Symbol hardware product warranty statement, go to: <http://www.symbol.com/warranty>

## About Symbol Technologies

Symbol Technologies, Inc., The Enterprise Mobility Company™, is a recognized worldwide leader in enterprise mobility, delivering products and solutions that capture, move and manage information in real time to and from the point of business activity. Symbol enterprise mobility solutions integrate advanced data capture products, radio frequency identification technology, mobile computing platforms, wireless infrastructure, mobility software and world-class services programs. Symbol enterprise mobility products and solutions are proven to increase workforce productivity, reduce operating costs, drive operational efficiencies and realize competitive advantages for the world's leading companies. More information is available at [www.symbol.com](http://www.symbol.com)



Corporate Headquarters  
**Symbol Technologies, Inc.**  
One Symbol Plaza  
Holtsville, NY 11742-1300  
TEL: +1.800.722.6234  
+1.631.738.2400  
FAX: +1.631.738.5990

For Asia Pacific Area  
**Symbol Technologies Asia, Inc.**  
(Singapore Branch)  
Asia Pacific Division  
230 Victoria Street #12-06/10  
Bugis Junction Office Tower  
Singapore 188024  
TEL: +65.6796.9600  
FAX: +65.6796.7199

For Europe, Middle East and Africa  
**Symbol Technologies**  
EMEA Division  
Symbol Place, Winnersh Triangle  
Berkshire, England RG41 5TP  
TEL: +44.118.9457000  
FAX: +44.118.9457500

For North America, Latin America and Canada  
**Symbol Technologies**  
The Americas  
One Symbol Plaza  
Holtsville, NY 11742-1300  
TEL: +1.800.722.6234  
+1.631.738.2400  
FAX: +1.631.738.5990

**Symbol Web Site**  
For a complete list of Symbol subsidiaries and business partners worldwide contact us at:  
[www.symbol.com](http://www.symbol.com)  
**E-mail**  
[info@symbol.com](mailto:info@symbol.com)



Part No. DS-LS3008 Printed in USA 07/06 © Copyright 2006 Symbol Technologies, Inc. All rights reserved. Symbol is an ISO 9001 and ISO 9002 UKAS, RVC, and RAB Registered company, as scope definitions apply. Specifications are subject to change without notice. Symbol® is a registered trademark of Symbol Technologies, Inc. All other trademarks and service marks are proprietary to their respective owners. For system, product or services availability and specific information within your country, please contact your local Symbol Technologies office or Business Partner.