



# Zebra® Z Series™ Metal

Thermal, On-Demand, Metal Bar Code Printers

## Z4Mplus™ and Z6Mplus™—Sleek with Speed

Processing labels fast is a breeze with the Z4Mplus and Z6Mplus industrial and commercial bar code printers. At 10 inches (254 mm) per second, these Zebra printers output labels quickly and efficiently, maximizing production and minimizing wait time for demanding jobs like variable-information applications. The Z4Mplus and Z6Mplus die-cast metal construction means reliability and top performance for industrial environments and distribution centers.

## Competitive Performers, Competitive Price

Z Series printers stand up to the competition, in terms of both performance and price. Rely on these top-of-the-line performers to get the job done, cost-effectively. Up to twice as fast as CompactFlash, Zebra's powered up Flash memory option drives productivity farther than ever before! The Z Series offers many standard features per dollar, including ZebraLink™ with Alert and WebView for centralized printer management. With an internal Ethernet option, super-fast external memory options, industry-leading throughput, and complex multi-language font support, the Z4Mplus and Z6Mplus are unbeatable commercial printers.

On top of the hard-working durability and easy use of these die-cast metal frame printers, the newly speed-optimized Z4Mplus and Z6Mplus are perfect for:

- Work in process
- Order fulfillment
- Compliance labeling
- Distribution
- Shipping/Receiving
- Hospitality/Transportation ticketing



Connect with it. Count on it.™

# Z4Mplus Z6Mplus



## Specifications at a Glance\*

### STANDARD FEATURES

Print methods: Thermal transfer or direct thermal  
 Construction: Die-cast aluminum base, frame and printhead mechanism  
 ZebraLink™  
 Metal media cover with large clear window  
 Zebra E<sup>3</sup>™ Printhead Energy Control  
 Auto-calibration  
 Real-time clock  
 Auto-ranging (110 V–220 V) power supply  
 Color-coded operator cues  
 Back-lit LCD control panel

### Zebra Programming Language

ZPL® & ZPL II®—universal language for Zebra® printers  
 ZBI™—works with ZPL to control and interpret text and data streams from peripherals and non-ZPL printer programming languages. Transmits captured data over LAN, WAN, or wireless network via e-mail or TCP/IP messaging.

### OPERATING CHARACTERISTICS

#### Environment

Operating Temp. 32° F/0° C to 104° F/40° C (Direct Thermal)  
 Operating Temp. 40° F/5° C to 104° F/40° C (Thermal Transfer)  
 Storage Temp. -40° F/-40° C to 140° F/60° C  
 Operating Humidity 20-85% non-condensing  
 Storage Humidity 5-85% non-condensing

#### Electrical

Universal auto-ranging (PFC-compliant) power supply 90-265 VAC; 48-62 Hz; 5A fused

#### Communication Interface Capabilities

RS-232C serial port  
 High-speed, IEEE1284, bi-directional parallel interface  
 ZebraNet® PrintServer II

#### Agency Approvals and Product Markings

Agencies: IEC60950, EN55024 Class B, EN55024, EN61000-3-2, EN61000-3-3,  
 Markings: cULus, CE Marking, FCC-B, ICES-003, VCCI, C-Tick, NOM, IRAM, CCC, GOST-R, BSMI

### MEDIA CHARACTERISTICS

#### Labels

Max. Roll Size: 8"/203 mm O.D. on a 3"/76 mm I.D. core  
 Thickness (label & liner): .0023"/.058 mm to .01"/.25 mm  
 Maximum non-continuous label length 39"/991 mm  
 Media Types: Continuous or fanfold, die-cut, notched, tag stock, black mark, perforated  
 For optimum print quality and print engine performance, use Genuine Zebra Supplies.

#### Ribbons

Max. Roll Size: 3.2"/81.3 mm O.D. on a 1"/25.4 mm I.D. core  
 Standard Lengths: 1476/450 m; provides 3:1 media roll to ribbon ratios  
 Ribbon Setup: Ribbon wound ink side out  
 Ribbon is recommended to be at least as wide as media.

### FONTS/GRAPHICS/SYMBOLOLOGIES

#### Fonts and Character Sets

7 bitmapped, 1 smooth scalable (CG Triumvirate™ Bold Condensed)  
 Sets: International character sets supporting the following code pages:  
 IBM® Code Page 850 International character set  
 Optional European and Asian font sets

#### Graphic Features

Supports user-defined fonts and graphics—including custom logos  
 ZPL II drawing commands—including boxes and lines

#### Bar Code Symbolologies

Linear Bar Codes: Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case C Codes, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2 or 5 digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar, Planet Code, RSS  
 2-Dimensional: Codablock, PDF417, Code 49, Data Matrix, MaxiCode, QR Code, Micro PDF417, TLC 39, RSS

### OPTIONS AND ACCESSORIES

Standard Memory: 2 MB Flash, 8MB DRAM  
 Optional Memory: Up to 32 MB additional Flash via PCMCIA; Up to 256 MB additional ATA format via PCMCIA or CompactFlash cards  
 Cutter with catch tray  
 Peel—a front mount, passive peel option with no liner take-up  
 Liner take-up (works with peel option)—full roll liner take-up spindle (fits standard base; Z4Mplus only)  
 Rewind—internally rewinds full label roll on three-inch core (comes with taller, non-standard printer base)  
 Memory Socket Card PCMCIA: Supports PCMCIA cards up to 32 MB  
 CompactFlash: Supports CompactFlash cards up to 256 MB  
 Adjustable transmissive sensor  
 ZebraNet® PrintServer II  
 BAR-ONE® 6.04 software  
 RS-422/485 serial port adapter  
 European and Asian font sets

Quicker first label out and shorter print times make the Z Series printers up to **five times faster** than before when processing most variable-information labels.

#### MAXIMUM PRINT AREA

(STANDARD MEMORY, CONTINUOUS MEDIA)

<b>Z4Mplus</b>	<b>Z6Mplus</b>
Width: 4.09"/104 mm	Width: 6.6"/168 mm
Length with 203 dpi: 174"/4,420 mm	Length with 203 dpi: 116"/2,946 mm
Length with 300 dpi: 73"/1,851 mm	Length with 300 dpi: 49"/1,254 mm

#### PHYSICAL CHARACTERISTICS

<b>Z4Mplus</b>	<b>Z6Mplus</b>
Width: 10.93"/278 mm	Width: 13.43"/341 mm
Depth: 18.69"/475 mm	Depth: 18.69"/475 mm
Height: 13.32"/338 mm	Height: 13.32"/338 mm
Weight: 32.4 lbs/15 kg	Weight: 34.7 lbs/16 kg

#### MEDIA SPECIFICATIONS

<b>Z4Mplus</b>	<b>Z6Mplus</b>
Label and liner width:	Label and liner width:
Min: 1"/25.4 mm–	Min: 2"/51 mm–
Max (Tear/Cutter): 4.5"/114 mm	Max (Tear/Cutter): 7"/178 mm
Max (Peel/Rewind): 4.25"/108 mm	Max (Peel/Rewind): 6.75"/171 mm
Ribbon width: 2"/51 mm–	Ribbon width: 2"/51 mm–
4.33"/110 mm	6.85"/174 mm

#### RESOLUTION

203 dpi/8 dots per mm; 300 dpi/12 dots per mm

#### MAXIMUM PRINT SPEED

203 dpi/10 ips; 300 dpi/6 ips

#### MEMORY

Standard: 2 MB Flash, 8MB DRAM  
 Optional: Up to 32 MB additional Flash via PCMCIA; Up to 256 MB additional ATA format via PCMCIA or CompactFlash cards

\*Specifications subject to change without notice. Copyright 2003 ZIH Corp. Z4Mplus, Z6Mplus, ZBI and ZebraLink are trademarks and Zebra, BAR-ONE, ZebraNet, ZPL, ZPL II and E<sup>3</sup> are registered trademarks of ZIH Corp. All rights reserved. All other trademarks are the property of their respective owners.

**HEADQUARTERS** Zebra Technologies International, LLC **T:** +1 847 793 2600 or +1 800 423 0442 **F:** +1 847 913 8766  
**ADDRESS:** 333 Corporate Woods Parkway, Vernon Hills, IL 60061-3109 U.S.A. **WEB:** www.zebra.com

**OTHER LOCATIONS** **USA:** California, Florida, Rhode Island, Wisconsin **EUROPE:** Denmark, France, Germany, Italy, South Africa, United Kingdom **ASIA-PACIFIC:** Australia, China, Japan, Singapore, South Korea **LATIN AMERICA:** Argentina, Brazil, Mexico **MIDDLE EAST:** United Arab Emirates



An ISO 9001 registered company  
 GSA#: GS-35F-0268N  
 ©2003 ZIH Corp. Printed in U.S.A.  
 #13391L Rev. 1 (9/03) xM